

## **Ultem Foam XP080** Americas: COMMERCIAL

ULTEM foam is a polyetherimide based thermoplastic foam with excellent flame, smoke and toxicity performance. The material combines a high strength to weight ratio with low moisture absorption. The foam also possesses excellent dielectric properties. ULTEM foam is targeted at applications where structural fire performance, radar transparency, or extreme hot or cold environments are required. ULTEM foam is thermoformable and compatible with phenolic pre-pregs. Information on processing or secondary operations is available upon request.

YPICAL PROPERTIES <sup>1</sup>	TYPICAL VALUE	Unit	Standard
MECHANICAL			
Compressive Strength perpendicular to plane	12	kgf/cm²	ASTM D 1621
Compressive Modulus perpendicular to plane	720	kgf/cm²	ASTM D 1621
Tensile Strength in plane	17	kgf/cm²	ASTM D 638
Tensile Modulus in plane	370	kgf/cm²	ASTM D 638
Shear Strength	10	kgf/cm²	ASTM C 273
Shear Modulus	190	kgf/cm²	ASTM C 273
Impact Strength	0.8	cm-kgf/cm <sup>2</sup>	ISO R179
THERMAL			
Coefficient of Thermal Conductivity	0.037	W/m-K	ASTM C 518
PHYSICAL			
Density	0	g/cm³	ASTM D 1622
Water Absorption	4	%	ASTM C 272
FLAME CHARACTERISTICS			
OSU total heat release (2 minute test)	<55	kW-min/m²	FAR 25.853
OSU peak heat release rate (5 minute test)	<55	kW/m²	FAR 25.853
Smoke Density	<10	Ds	FAR 25.853
Smoke Toxicity	PASSES	-	OEM BSS
Smoke Toxicity	PASSES	-	OEM ABD
Insulation Radiant Panel	PASSES	-	FAR 25.856
Vertical Burn at 60 Seconds	PASSES	-	FAR 25.853

## Source GMD, last updated:

PLEASE CONTACT YOUR LOCAL SALES OFFICE FOR AVAILABILITY IN YOUR AREA.

DISCLAIMER: THE MATERIALS, PRODUCTS AND SERVICES OF SABIC INNOVATIVE PLASTICS HOLDING BY, ITS SUBSIDIARIES AND AFFILIATES ("SELLER"), ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH CAN BE FOUND AT http://www.sabic-ip.com.and Are Available upon request. Although any information or recommendation contained herein is given in good fairly, seller makes no warranty or guaranties, express or implications. Except a seller standard conditions of subject and the seller's products services or recommendations for the user's particular use through appropriate end-use testing and analysis. Nothing in any document or oral statement shall be deemed to after or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed Seller. No statement Seller concerning a possible use of any product, services or design is intended, or should be construed, to grant any license under any patent or other intellectual property right. SABIC Innovative Plastics is a trademark of SABIC Holding Europe B.V.

© 2013 SABIC Innovative Plastics Holding BV.All rights reserved

<sup>(1)</sup> Typical values only. Variations within normal tolerances are possible for various colors. All values are measured after at least 48 hours storage at 23°C/50% relative humidity. All properties, except the melt volume and melt flow rates, are measured on injection molded samples. All samples tested under ISO test standards are prepared according to ISO 294.

<sup>(2)</sup> Only typical data for selection purposes. Not to be used for part or tool design.
(3) This rating is not intended to reflect hazards presented by this or any other material under actual fire

conditions.

(4) Internal measurements according to UL standards.
(5) Measurements made from laboratory test coupon. Actual shrinkage may vary outside of range due to differences in processing conditions, equipment, part geometry and tool design. It is recommended that mo shrinkage studies be performed with surrogate or legacy tooling prior to cutting tools for new molded article.



Ultem Foam XP080 Americas: COMMERCIAL



## ООО «Торгово-Строительная Компания Империя»

109382, Россия, г.Москва, ул.Нижние поля, 31 +7(495)646-81-65 info@tbc-empire.ru www.tbc-empire.ru

## **LLC TBC Empire**

109382, Russia, Moscow, Nizhniye polya,31 +7(495)646-81-65 info@tbc-empire.ru www.tbc-empire.ru

Source GMD, last updated:

PLEASE CONTACT YOUR LOCAL SALES OFFICE FOR AVAILABILITY IN YOUR AREA.

DISCLAIMER: THE MATERIALS, PRODUCTS AND SERVICES OF SABIC INNOVATIVE PLASTICS HOLDING BY, ITS SUBSIDIARIES AND AFFILIATES ("SELLER"), ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH CAN BE FOUND AT http://www.sabic-ip.com.AND ARE AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION OR RECOMMENDATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SELLER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR RIMPLIED, (I) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (II) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING SELLER'S PRODUCTS, SERVICES OR RECOMMENDATIONS. EXCEPT AS PROVIDED IN SELLER'S STANDARD CONDITIONS OF SALE, SELLER SHALL NOT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user is responsible for making its own determination as to the suitability of Seller's products, services or recommendations for the user's particular use through appropriate end-use testing and analysis. Nothing in any document or oral statement shall be deemed to alter or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed Seller. No statement Seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right. SABIC Innovative Plastics is a trademark of SABIC Holding Europe B.V.

Ultem Foam

©2013SABIC Innovative Plastics Holding BV.All rights reserved